

# Cut Large Logs to Precise Lengths **HWP-165 Firewood Blocker**

## **Precise Length, Every Time**

Set the length round you want and cut every round to that length from up to 22-inch diameter logs – all from the safety and comfort of the host machine's cab.



## **Log to Measured Rounds**

The HWP-165 goes to the log and lifts it. Then to the firewood pile or boiler where it helps center the log, cuts rounds to precise lengths and ejects consistent length rounds onto a pile or into a container – all from the safety and comfort of the machine's cab.



## **Universal Quick Attach**

This processor can be attached to most skid steer, tractor, excavator and front loader host machines in minutes using the Universal Quick Attach system.



# Cut Large Logs to Precise Lengths **HWP-165 Firewood Blocker**

## Specifications



<b>SPECS</b>	<b>VALUE</b>
Length	Working Configuration 144" (366 cm)
Width	68" (173 cm)
Height	70" (178 cm)
Weight	1,692 lbs. (768 kg)
Minimum Pressure	2,850 PSI (196 bar)
Flow	15.5 gpm (57l/min)
Connections	1-Pressure, 1-Return, 1-Case Drain
Maximum Log Dia.	22" (56 cm)
Maximum Log Length	12' (3.66 m)
Minimum Log Length	6' (1.82 m)
Firewood Cut Length	16" to 22" (40 - 56 cm) in 2" increments
Saw Bar	31" (82 cm) Speedmax XL
Saw Chain	97 DL 0.404 pitch/18HX Series
Saw Motor	Bent Axis Piston (Industrial)
Saw Oiler	Automatic 2 qt (1.89 l) Tank
Maximum Saw Cut	22" (56 cm)
In-feed	Feed chain/roller arm feeds log to saw stop
Mounting	Universal Quick Attach SAE Spec J2513