

# Splits up to 22-inch Logs in One Pass **HWP-135 Lightning Splitter**

## **One Motion to Split & Eject**

Using the HWP-135 Lightning Splitter, toss the round in its trough and watch it split and be ejected on to the pile or into your choice of containers. The Lightning Splitter quickly spits up to 22" rounds in a single pass.



## **One or Two Person Operation**

The basic model HWP-135 is operated using the host machine's cab controls and works best with two persons, one in the cab and one loading rounds. The XLT model can be operated by one person on the ground loading rounds and controlling the processor.



## **Universal Quick Attach**

This processor can be attached to most skid steer, tractor, excavator and front loader host machines in minutes using their Universal Quick Attach system.



# Splits up to 22-inch Logs in One Pass

## HWP-135 Lightning Splitter

### Specifications



SPECS	VALUE
Length	80" (203 cm)
Width	24" (61 cm)
Height	29" (74 cm)
Weight (XLT Model)	747 lbs. (339 kg)
Material	3/8" Steel
Minimum Pressure	2,850 PSI (196 bar)
Flow	15.5 GPM
Connections	1-Pressure, 1-Return
Maximum Log Dia.	22" (56 cm)
Maximum Log Length	22" (56 cm)
Splitter Cylinder	Custom 3.5" Bore x 24" Stroke
Splitter Force	28,500 lbs. @3,000 psi
Spitting Wedge	4, 6 or 8-way Adjustable
Mounting	Universal Quick Attach SAE Spec J251